

1.3Mp CMOS HD Network Dome Camera



Main Features

- ⇒ 1/3" 1.3 Megapixel CMOS image sensor
- ⇒ High-Performance DSP
- ⇒ H.264 video compression and JPEG image capture
- ⇒ Upto 1.3M(1280×960) / 720P(1280×720) / D1 (704×576/704×480) Image Resolution
- ⇒ Dual encoding streams supported
- ⇒ Remote Operation: Monitor, PTZ control, Playback, System setting, File download, Log information, Maintenance & Upgrade
- ⇒ Built-in 2.8mm/3.6mm/6mm/8mm lens
- ⇒ Built-in Web server, CMOB & KVMS(CMS)

Feature	Specification
Image Sensor	1/3" 1.3 Megapixel CMOS
Minimum Illumination	0.1LUX/F1.2
Shutter Speed	Auto/Manual, 1/3~1/10000s
White Balance	Auto/Manual
Lens	3.6mm (2.8mm/6mm/8mm optional)
Video Compression	H.264/MJPEG/JPEG
Video Streaming	1.3M (1~15fps)+ D1(1~15fps), 720P(1~25fps)+ D1(1~25fps)
Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480)
Frame Rate	1~25fps
Event Notification	HTTP, FTP, SMTP
Interface	RJ-45 (10/100Base-T)
Protocol	HTTP, TCP/IP, IPv4/IPv6, ARP, IGMP, ICMP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, UPNP, NTP, Bonjour, SNMP, Onvif
Operating Temperature	-10°C~+50°C, 10%~90%
Power Source	DC12V, PoE
Power Consumption	Max.1.5W
Dimension	54mm x ϕ 110mm
Weight	0.25kg